



PART No		PART No.	
2344-1	.5 MFD	2290	2 MEG
2344-2	.5 "	2366	17500 Ω
2405	.0001 "	2299	175 Ω
2346	.0001 "	2341	3500 Ω
2347	.00025 "	2340	1750 Ω
2343	2 "	2436	10 Ω
2345	1 "	2364	600 Ω
		2339	1000 Ω

SERIES 40 HAS 5000 FIELD COIL.

EVEREADY—Series 40
Line Voltage 117—Set on 115 Volt Tap—Volume Control Position Full

TUBE NO. IN ORDER	TYPE OF TUBE	POSITION OF TUBE 1ST R.F. DET. ETC.	READINGS, PLUG IN SOCKET OF SET									
			TUBE OUT				TUBE IN TESTER					
			A VOLTS	B VOLTS	A VOLTS	B VOLTS	2 VOLTS CONTROL - HEATER GRID	CATHODE NORMAL PLATE	NORMAL PLATE M.A.	PLATE CHARGE TEST	PLATE M.A.	SCREEN GRID VOLTS
1	227	1st RF	2.15	109	2.45	100	6	-	2.6	6	3.4	
2	227	2nd RF	2.15	109	2.45	100	6	-	2.6	6	3.4	
3	227	3rd RF	2.15	109	2.45	100	6	-	2.6	6	3.4	
4	227	Det.	2.15	109	2.45	50	0	-	3	3.1	.1	
5	227	1st AF	2.15	109	2.45	100	4.5	-	3	4.5	1.5	
6	245	2nd AF	2.6	300	2.5	250	50	-	26	30	4	
7	245	2nd AF	2.6	300	2.5	250	50	-	26	30	4	
8	280	Rect.	5.2	-	5.0	-	-	-	100	-	-	

EVEREADY
SERIES 30 (1929)
(USES 171A3)
SERIES 40 (EARLY 1930)
(USES 2453)
CIRCUITS THE SAME IN OTHER RESPECTS

